



CSA Standard PVC Conduit

Rigid PVC Conduit, DB2 Rigid PVC conduit, Electrical Nonmetallic Tubing



IDEAS OF NEW DESIGN CSA STANDARD
CONDUIT SYSTEMS THAT PROTECT
PEOPLE AND THEIR PROPERTY

RIGID PVC CONDUIT



Item No.	Trade Size	Metric Size	Average OD	Average ID
			Inches	Inches
HH-CSRCA	1/2	16	0.840	0.622
HH-CSRCB	3/4	21	1.050	0.824
HH-CSRCC	1	27	1.315	1.049
HH-CSRCD	1-1/4	35	1.660	1.380
HH-CSRCE	1-1/2	41	1.900	1.610
HH-CSRCE	2	53	2.375	2.067
HH-CSRCE	2-1/2	63	2.875	2.469
HH-CSRCH	3	78	3.500	3.068
HH-CSRCH	3-1/2	91	4.000	3.548
HH-CSRCH	4	103	4.500	4.026
HH-CSRCK	5	129	5.563	5.047
HH-CSRCL	6	155	6.625	6.065
HH-CSRCL	8	200	8.620	7.980

Standard: CSA and UL

Color can be made in grey and orange.

PVC material with great corrosion resistant.

Sunlight resistant.

Fire resistant.

Chemical resistant.


Nonconducting.

Concrete tight.

Rated for use with 75°C conductors.

Provided with nominal lengths in 10ft or 20ft.

Suitable for exposed, concrete encased and direct burial applications.




DB2 Rigid PVC Conduit



Standard: CSA
Color can be made in grey and orange.
PVC material with great corrosion resistant.
Fire resistant.
Chemical resistant.
Nonconducting.
Concrete tight.
Provided with nominal length in 10ft or 20ft.
Intended for use in concrete encased or masonry and direct burial applications.

Item No.	Trade Size	Metric Size	Average OD		Average ID
			min	max	mm
HH-DB2RCA	2	53	57.00	57.30	50.80
HH-DB2RCB	3	78	82.35	82.75	76.20
HH-DB2RCC	3-1/2	91	94.50	95.00	88.40
HH-DB2RCD	4	103	106.85	107.30	100.10
HH-DB2RCE	4-1/2	116	121.20	121.70	114.30
HH-DB2RCF	5	129	134.35	134.85	126.35
HH-DB2RCG	6	155	159.10	159.65	149.75



Electrical Nonmetallic Tubing



Item No.	Size	Average OD	Average ID	length per Coil	
		Inches	Inches	unit	ft
HH-ENTA	1/2	0.840	0.602	roll	100
HH-ENTB	3/4	1.050	0.804	roll	100
HH-ENTC	1	1.315	1.029	roll	100
HH-ENTD	1-1/4	1.660	1.360	roll	100
HH-ENTE	1-1/2	1.900	1.590	roll	100
HH-ENTF	2	2.375	2.047	roll	100

Manufacturer suggest that our ENT tubing should not be stored outdoors where subjected to direct sunlight without protective covering, i.e. packaging or tarps.

Standard: CSA and UL

Color can be made in grey and blue.

PVC material with great corrosion resistant.

Fire resistant,

Impact resistant.

Deflection resistant.

Concrete tight.

Intended for encased in concrete, concealed in walls or ceilings, or in direct burial applications.





DONGGUAN HOPEHEAD DECORATIVE MATERIALS Co., Ltd

 Building 1, Lakeshore RD 6, Dalingshan Town, Dongguan City,
Guandong Province, China.

 400-718-9968

 info@ledestube.com

 www.ledestube.com